

Pipe Data

PIPE SIZE	OD	Schedule 10				Standard				Extra Strong			
		ID	Wall	lbs/ft	I in ⁴	ID	Wall	lbs/ft	I in ⁴	ID	Wall	lbs/ft	I in ⁴
1/2	0.84	~	~	~	~	0.622	0.11	0.84	0.017	0.55	0.15	1.08	0.020
3/4	1.05	0.88	0.08	0.85	0.030	0.82	0.11	1.12	0.037	0.74	0.15	1.46	0.045
1	1.32	1.10	0.11	1.39	0.076	1.05	0.13	1.66	0.087	0.96	0.18	2.15	0.106
1 1/4	1.66	1.44	0.11	1.78	0.160	1.38	0.14	2.25	0.195	1.28	0.19	2.96	0.242
1 1/2	1.90	1.68	0.11	2.06	0.247	1.61	0.15	2.69	0.310	1.50	0.20	3.59	0.391
2	2.38	2.16	0.11	2.61	0.499	2.07	0.15	3.61	0.666	1.94	0.22	4.96	0.868
2 1/2	2.88	2.64	0.12	3.49	0.987	2.47	0.20	5.73	1.530	2.32	0.28	7.57	1.924
3	3.50	3.26	0.12	4.28	1.82	3.07	0.22	7.49	3.02	2.90	0.30	10.13	3.89
3 1/2	4.00	3.76	0.12	4.91	2.76	3.55	0.23	9.00	4.79	3.36	0.32	12.36	6.28
4	4.50	4.26	0.12	5.55	3.96	4.03	0.24	10.66	7.23	3.83	0.34	14.81	9.61
5	5.56	5.30	0.13	7.68	8.43	5.05	0.26	14.45	15.16	4.81	0.38	20.54	20.67
6	6.63	6.36	0.13	9.18	14.40	6.07	0.28	18.75	28.14	5.76	0.43	28.24	40.49
8	8.63	8.33	0.15	13.24	35.41	7.98	0.32	28.22	72.49	7.63	0.50	42.88	105.72
10	10.75	10.42	0.17	18.44	76.86	10.02	0.37	40.01	160.73	9.75	0.50	54.10	211.95
12	12.75	12.39	0.18	23.88	140.42	12.00	0.38	48.99	279.34	11.75	0.50	64.65	361.54
14	14.00	13.50	0.25	36.29	255.30	13.25	0.38	53.93	372.76	13.00	0.50	71.25	483.76
16	16.00	15.50	0.25	41.56	383.66	15.25	0.38	61.85	562.08	15.00	0.50	81.81	731.94
18	18.00	17.50	0.25	46.84	549.14	17.25	0.38	69.77	806.63	17.00	0.50	92.36	1053.17
20	20.00	19.50	0.25	52.12	756.43	19.25	0.38	77.68	1113.47	19.00	0.50	102.92	1456.86
24	24.00	23.50	0.25	62.67	1315.34	23.25	0.38	93.52	1942.30	23.00	0.50	124.03	2549.35

All data in imperial units

transdynamics.ca